










ANCHOR SYSTEMS

STYLE	EXAMPLE	DESCRIPTION
"A"		1/4" DIA. X 4" (S.S. DOWEL) OR 3/8" DIA. X 6" (S.S. DOWEL) OR 1/2" DIA. X 6" (S.S. DOWEL)
"B"		1/8" T. X 1" W. X (O.A.) W / 1" TURN DOWN W / 5/16" DIA. HOLE CENTERED 1" IN FROM END (S.S. STRAP ANCHOR)
"C"		1/8" T. X 1" W. X (O.A.) W / 1" TURN DOWN @ BOTH ENDS (S.S. STRAP ANCHOR)
"D"		1/8" T. X 1" W. X (O.A.) W / 1" SPLIT TAIL W / 5/16" DIA. HOLE CENTERED 1" IN FROM END (S.S. STRAP ANCHOR)
"E"		1/8" T. X 1" W. X (O.A.) W / 1" SPLIT TAIL AND 1" TURN DOWN @ OPP. END (S.S. STRAP ANCHOR)
"F"		DIA. X LONG EYE BOLT W / 3" OF THREAD / NUT & WASHER W / LOOSE DIA. X LONG (S.S. DOWEL) (WELD EYE SHUT)
"G"		DIA. X LONG (S.S. THREADED DOWEL)
"H"		1/8" T. X 1" W. X (O.A.) W / 2 - 5/16" DIA. HOLES CENTERED 1" IN FROM EACH END W / 1/4" DIA. X LONG (S.S. DOWEL) LOOSE FIT IN ONE END (S.S. STRAP ANCHOR)
"I"		1/8" T. X 1" W. X (O.A.) W / 2 - 5/16" DIA. HOLES CENTERED 1" IN FROM EACH END (S.S. STRAP ANCHOR)

Contractor to bend anchor as required and fasten or weld to back-up.

All pieces type 302/304 stainless steel unless noted otherwise.